

Demo 8 | 2014

Technische Spezifikationen:

RAHMEN	M5 manipulated alloy, 1.5" forged headtube, 150mm rear spacing, compact race design, ISCG '05 mount, cartridge bearing rear shock mount, rear derailleur protector, 200mm travel
DÄMPFER	Custom FOX VAN RC, coil over w/ piggy back, compression and reb adj., 9.5x3", XS: 300, S: 350, M: 400, L: 450
GABEL	RockShox Boxxer RC, alloy steerer, compression and rebound adj., 20mm Maxle DH thru-axle, XS/S: extra-soft spring, M: soft spring, L: medium spring, 200mm travel
STEUERSATZ	1-1/2" integrated for 1-1/8" steerer, cartridge bearings
VORBAU	Specialized Direct Mount, 6061 alloy, 4-bolt, 31.8mm clamp
LENKER	Specialized Demo, low-rise, 7050 alloy, 780mm wide, 8-degree backsweep, 6-degree upsweep, 31.8mm
LENKERGRIFFE	Specialized Sip Grip, light lock-on, half-waffle aramid-infused, S/M: regular, Others: XL thickness
VORDERRADBREMSE	Custom Avid Elixir 7 Trail, 4-piston caliper, steel backed metallic pad, 200mm rotor
HINTERRADBREMSE	Custom Avid Elixir 7 Trail, 4-piston caliper, steel backed metallic pad, 180mm rotor
BREMSHEBEL	Custom Avid Elixir 7 Trail, hydraulic disc, tool-less reach adj.
UMWERFER	
SCHALTWERK	SRAM X9 Type 2, 10-speed, mid cage
SCHALTHEBEL	SRAM X7, 10-speed, aluminum trigger, w/ MatchMaker clamp
KASSETTE	Shimano Tiagra, 10-speed, 11-25
KETTE	SRAM PC 1031, 10-speed, PowerLink
KURBELGARNITUR	Custom SRAM Descendant, PF30 spindle, 7050 alloy arms, w/ Gamut P-30 chain guide
KETTENBLÄTTER	32T
INNENLAGER	SRAM PF30 DH, 83mm shell
PEDALE	Specialized Bennies, 6061 alloy body, sealed cartridge, 4.5mm removable pins
FELGEN	Roval DH 26, alloy disc, 30mm wide w/eyelets, 32h
VORDERRADNABE	Specialized Hi Lo disc, sealed cartridge bearings, 20mm thru-axle, 32h
HINTERRADNABE	Specialized Hi Lo disc, 150mm, hollow 12mm Cr-Mo axle w/ RD guard, 32h
SPEICHEN	DT Industry Stainless, 3X front/rear 2.0
VORDERREIFEN	Specialized Butcher DH, 26x2.5", wire bead, soft dual-compound, 60 TPI
HINTERREIFEN	Specialized Butcher DH, 26x2.5", wire bead, soft dual-compound, 60 TPI
SCHLÄUCHE	Standard presta valve
SATTEL	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SATTELSTÜTZE	Specialized 6061 alloy, 2-bolt micro-adjust, no offset, 30.9mm, 300mm
SATTELSTÜTZKLEMME	Specialized 7050 hard anodized alloy, single bolt, 34.9mm

Änderungen von Spezifikationen vorbehalten.

Geometrie

Größe	XS	S	M	L
Gesamthöhe bis Oberkante Steuerl	936mm	936mm	936mm	936mm
Hinterbaulänge (mm)	421mm	421mm	421mm	421mm
Kurbellänge	165mm	165mm	165mm	165mm
Lenkerbreite	750mm	750mm	750mm	750mm
Lenkwinkel - flache Einstellung	64°	64°	64°	64°
Lenkwinkel - hohe Einstellung	64.8°	64.8°	64.8°	64.8°
Oberrohrlänge horizontal	540mm	560mm	580mm	597mm
Oberrohrlänge tatsächlich	485mm	504mm	517mm	530mm
Radstand	1151mm	1171mm	1191mm	1208mm
Reach	390mm	410mm	430mm	447mm
Sitzrohrlänge	300mm	300mm	300mm	300mm
Sitzrohrlänge (Mitte Tretl. bis Ende	394mm	394mm	419mm	458mm
Sitzrohrwinkel effektiv - flache Einst	76°	76°	76°	76°
Sitzrohrwinkel effektiv - hohe Einst	76.8°	76.8°	76.8°	76.8°
Sitzrohrwinkel tatsächlich - flache E	62°	62°	62°	62°
Sitzrohrwinkel tatsächlich - hohe Ei	62.8°	62.8°	62.8°	62.8°
Stack	593mm	593mm	593mm	593mm
Steuerrohrhöhe	112mm	112mm	112mm	112mm
Tretlagerhöhe - hohe Einstellung	353mm	353mm	353mm	353mm
Tretlagerhöhe - niedrige Einstellunç	343mm	343mm	343mm	343mm
Vorbaulänge	45mm	45mm	45mm	45mm
Überstandshöhe (mm)	717mm	717mm	722mm	731mm