

# Enduro Elite 650b 2015

## Technische Spezifikationen:

<b>RAHMEN</b>	M5 aluminum, 650b geometry, tapered headtube, PF30 BB, ISCG '05 mount, internal Command Post IR routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 165mm travel
<b>GABEL</b>	RockShox Pike RC 650b, Solo Air spring, tapered alloy steerer, w/ compression, rebound adj., 15mm thru-axle, 160mm travel
STEUERSATZ	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
VORBAU	Specialized XC, 3D forged alloy, 4-bolt, 6-degree rise
LENKER	Specialized All-Mountain, low-rise, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 31.8mm
LENKERGRIFFE	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular thickness, Others: XL
VORDERRADBREMSE	SRAM Guide R, metallic pads, Guide R caliper, 200mm Centerline rotor
HINTERRADBREMSE	SRAM Guide R, metallic pads, Guide R caliper, 180mm Centerline rotor
BREMSHEBEL	SRAM Guide R, alloy lever, w/ reach adjust
SCHALTWERK	SRAM X1, 11-speed, alloy cage
SCHALTHEBEL	SRAM X1, 11-speed, trigger
KASSETTE	SRAM XG 1180, 11-speed, 10-42
KURBELGARNITUR	SRAM X1 1000, X SYNC ring, PF30, 34T, 94mm BCD spider
INNENLAGER	SRAM, PF30, OS press-in bearings, sealed cartridge
PEDALE	Resin test ride, w/ toe clips, CEN std.
FELGEN	Roval Traverse Fattie 650b, 29mm inner width, 24/28h
VORDERRADNABE	Roval Traverse, w/ 15/20mm thru-axle, 24h
HINTERRADNABE	Roval Traverse 650b 142+, XX1 driver body, DT Swiss Star Ratchet, 28h
SPEICHEN	DT Swiss Revolution
SATTEL	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SATTELSTÜTZE	Command Post IR, 3-position height adjustable, alien head design, bottom mount cable routing, v
SATTELSTÜTZKLEMME	Specialized 7050 alloy, single bolt, 34.9mm

Änderungen von Spezifikationen vorbehalten.

## Geometrie

Größe	S	M	L
Kettenstreben (mm)	422mm	422mm	422mm
Kurbellänge	170mm	175mm	175mm
Lenkerbreite	750mm	750mm	750mm
Lenkwinkel	65.5°	65.5°	65.5°
Oberrohrlänge horizontal	546mm	585mm	610mm
Oberrohrlänge tatsächlich	508mm	545mm	571mm
Radstand	1121mm	1160mm	1188mm
Reichweite (Reach)	386mm	421mm	443mm
Sattelstützen-Länge	380mm	425mm	425mm
Sitzrohrlänge (Mitte Tretl. bis Ende)	393mm	425mm	463mm
Sitzrohrwinkel effektiv	74.7°	74.6°	74.5°
Sitzrohrwinkel tatsächlich	68.5°	68.5°	69.5°
Stack	584mm	594mm	603mm
Steuerrohrlänge	110mm	120mm	130mm
Tretlagerabsenkung	2mm	2mm	2mm
Tretlagerhöhe	352mm	352mm	352mm
Vorbaulänge	60mm	60mm	75mm
Überstandshöhe (mm)	766mm	772mm	780mm