



MOTO GRN/BLK

BLK/RKT RED

Wir sind voll überzeugt von Karbon als Rahmenmaterial, aber die Leistungsfähigkeit unserer M5 Aluminium-Legierung muss sich nicht verstecken. Das Stumpjumper FSR Comp 650b ist wie maßgeschneidert für alle, die den Charakter der 650b Laufräder mögen und für ein potentes Trail-Bike keine Unsumme ausgeben wollen. Trotz seines geringen Gewichts ist das Chassis aus M5 Aluminium robust und steif, damit du dir keine Gedanken machen musst, wenn es mal gröber zur Sache geht. Auch bei den Komponenten haben erstklassige Funktion und Zuverlässigkeit oberste Priorität: RockShox Revelation Gabel, SRAM Schaltung, Shimano Bremsen und stabile Roval Laufräder. Auf dem Trail garantieren das perfekt abgestimmte Fahrwerk und die geniale Trail-Geometrie ultimativen Fahrspaß: Fox Dämpfer mit custom Rx Trail Tune, superkurze Kettenstreben, lange Front, niedriges Tretlager, flacher Steuerwinkel. Mit diesem Bike macht Shredden einfach nur Spaß!

- Das Trail-Chassis mit einem Rahmen aus M5 Aluminium vereint Robustheit, Steifigkeit und geringes Gewicht; der aktive und sensible FSR Hinterbau mit 150mm Federweg macht grobes Terrain beherrschbar.
- Der custom FOX FLOAT Evolution Dämpfer mit 150mm Federweg wird über unsere steife, direkte FSR 6-Pack Umlenkung angesteuert; leichte Abstimmung auf das Fahrergewicht dank AUTOSAG, Modi Climb/Trail/Descend, Rx Trail Tune für sensible, effiziente und harmonische Funktion bergauf wie bergab.
- Die RockShox Revelation RC3 650b mit perfekt abgestimmten 150mm Federweg kommt mit 15mm Maxle Ultimate Steckachse und sorgt für die nötige Kontrolle auf dem Trail.

SIZE	S	M	L	XL
Stack (mm)	590	599	608	617
Reichweite (Reach) (mm)	388	414	442	464
Steuerrohrlänge (mm)	95	105	115	125
Steuerrohrwinkel (deg)	67	67	67	67
Tretlagerhöhe (mm)	335	335	335	335
Tretlagerabsenkung (mm)	18	18	18	18
Nachlauf (mm)	104	104	104	104
Gabellänge (mm)	542	542	542	542
Fork Rake/Offset (mm)	42	42	42	42
Mitte Tretlager - Mitte Vorderachse (mm)	677	706	738	764
Kettenstreben (mm) (mm)	420	420	420	420
Radstand (mm)	1096	1126	1158	1184
Oberrohrlänge (horizontal) (mm)	553	585	618	646
Bike-Überstandshöhe (mm)	737	743	757	769
Sitzrohrlänge (mm)	396	430	468	523
Sitzrohrwinkel (deg)	74	74	74	74
Lenkerbreite (mm)	750	750	750	750
Vorbaulänge (mm)	45	60	60	60
Kurbellänge (mm)	170	175	175	175
Sattelstützen-Länge (mm)	390	430	430	430

SPECS	Technische Änderungen vorbehalten.
RAHMEN	M5 alloy, Trail 650b Geometry, internal cable routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, front derailleur compatible w/ Taco Blade, 150mm travel
DÄMPFER	Custom FOX FLOAT Evolution CTD, AUTOSAG, Rx Trail Tune, 197x47.6mm
GABEL	RockShox Revelation RC3 650b, Solo Air spring, 150mm travel, 3-position compression adjust, rebound adjust, tapered steerer, 42mm offset, 15mm Maxle Lite thru-axle
STEUERSATZ	Hella Flush, 1-1/8" and 1-1/2" threadless, Campy style upper w/ 1-1/2" lower, cartridge bearings
VORBAU	Specialized XC, 3D forged alloy, 4-bolt, 6-degree rise
LENKER	Specialized, 6000 alloy, 8-degree backsweep, 6-degree upsweep, 25mm rise, 750mm, 31.8mm
LENKERGRIFFE	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular thickness, L/XL: XL thickness
VORDERRADBREMSE	Shimano Deore, hydraulic disc, resin pads
HINTERRADBREMSE	Shimano Deore, hydraulic disc, resin pads
BREMSHEBEL	Shimano BL-M447, I-spec compatible
UMWERFER	SRAM X7, mid direct mount, w/ Taco Blade
SCHALTWERK	SRAM X9 Type 2, 10-speed, mid cage
SCHALTHEBEL	SRAM X7, 10-speed, w/ Matchmaker clamp
KASSETTE	SRAM PG-1030, 10-speed, 11-36t
KETTE	SRAM PC-1031, 10-speed, w/ PowerLink, nickel finish
KURBELGARNITUR	Custom SRAM S-1250, 7050 alloy arms, 10-speed double, PF30, 36/22T, 104/64mm BCD spider
INNENLAGER	SRAM, PF30, OS press-in bearings, sealed cartridge
PEDALE	Nylon, CEN std., w/ toe clips
FELGEN	Roval 650b, alloy, 29mm inner width, 24/28h
VORDERRADNABE	Specialized, Hi Lo disc, sealed cartridge bearings, 15mm thru-axle, 24h
HINTERRADNABE	Specialized, Hi Lo disc, 4x sealed cartridge bearings, 12mm thruaxle, 28h
SPEICHEN	DT Swiss Industry, stainless
VORDERREIFEN	Specialized Butcher Control, 60TPI, 2Bliss Ready, folding bead, 650bx2.3"
HINTERREIFEN	Specialized Purgatory Control, 60TPI, 2Bliss Ready, folding bead, 650bx2.3"
SCHLÄUCHE	Standard, Presta valve
SATTEL	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SATTELSTÜTZE	Command Post IRcc, cruiser control technology, micro-adjust height adjustable, alien head design, bottom mount cable routing, remote adjust lever, 30.9mm, S: 100mm travel, M/L/XL: 125mm
SATTELSTÜTZKLEMME	Specialized, 7050 alloy, single bolt, 34.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
93316-6302	STUMPJUMPER FSR COMP 650B	BLK/RKT RED	S
93316-6303			М
93316-6304			L
93316-6305			XL
93316-6502	STUMPJUMPER FSR COMP 650B	MOTO GRN/BLK	S
93316-6503			М
93316-6504			L
93316-6505	-		XL