

Jynx Comp 650b 2015

Technische Spezifikationen:

RAHMEN	Specialized A1 Premium Aluminum, Women's Recreational XC Geometry, women's butted tubesets, forged dropouts, replaceable derailleur hanger, kickstand mount
STEUERSATZ	1-1/8" upper/lower, Zerostack 44, steel cups, loose ball bearings
VORBAU	Specialized 3D forged alloy, 4-bolt, 7-degree rise, anti-corrosion hardware
LENKER	Specialized, low rise, double butted 6061 alloy, 9-degree backsweep, 5-degree upsweep, 15mm rise, 31.8mm
LENKERGRIFFE	Specialized Body Geometry XCT Women's, Kraton w/ gel, lock-on, closed end, 121.5mm
VORDERRADBREMSE	Tektro Auriga, hydraulic disc, resin/metallic pads, tooled women's reach adjust
HINTERRADBREMSE	Tektro Auriga, hydraulic disc, resin/metallic pads, tooled women's reach adjust
BREMSHEBEL	Tektro Auriga, hydraulic, women's short reach
UMWERFER	Shimano Altus, high mount, bottom swing, dual-pull
SCHALTWERK	Shimano Acera, 9-speed, SGS cage
SCHALTHEBEL	Shimano Altus Rapidfire Plus, SL type, w/ optical display
KASSETTE	Sunrace, 9-speed, 11-34
KETTE	KMC X9, 9-speed, reusable Missing Link
KURBELGARNITUR	Specialized Stout, forged alloy, 9-speed, square taper spindle
INNENLAGER	Square taper, cartridge bearings
PEDALE	Composite platform, w/ reflectors, 9/16"
FELGEN	Specialized Stout, 650b disc, alloy double-wall, pin joint, 25mm inner width, 32h
VORDERRADNABE	Specialized Hi Lo disc, alloy double-sealed, ground race, QR, 32h
HINTERRADNABE	Specialized Hi Lo disc, alloy, double-sealed, loose ball bearings, QR, 32h
SPEICHEN	Stainless, 14g, w/ brass nipple
VORDERREIFEN	Specialized Fast Trak Sport, 40TPI, wire bead, Flak Jacket protection, 650bx2.0"
HINTERREIFEN	Specialized Fast Trak Sport, 40TPI, wire bead, Flak Jacket protection, 650bx2.0"
SCHLÄUCHE	Standard, Schrader valve
SATTEL	Body Geometry Women's Riva Sport Plus, steel rails, 155mm
SATTELSTÜTZE	Alloy, 2-bolt, micro-adjust, 12.5mm offset, 30.9mm, anti-corrosion hardware
SATTELSTÜTZKLEMME	Alloy, nylon/glass fiber washer, QR, 34.9mm

Änderungen von Spezifikationen vorbehalten.

Geometrie

Größe	XS	SM	MD	LG
Hinterbaulänge (mm)	426mm	426mm	426mm	426mm
Kurbellänge	170mm	170mm	170mm	175mm
Lenkerbreite	640mm	640mm	660mm	660mm
Lenkwinkel	69.5°	69.5°	70°	70°
Mitte Tretlager - Mitte Vorderachse	606mm	626mm	633mm	653mm
Oberrohrlänge horizontal	527mm	547mm	569mm	589mm
Oberrohrlänge tatsächlich	527mm	537mm	548mm	565mm
Radstand	1027mm	1047mm	1054mm	1075mm
Reach	362mm	382mm	390mm	407mm
Sitzrohrlänge	350mm	350mm	350mm	350mm
Sitzrohrlänge (Mitte Tretl. bis Ende)	330mm	371mm	417mm	463mm
Sitzrohrwinkel	74°	74°	73°	73°
Stack	576mm	576mm	587mm	597mm
Steuerrohrlänge	100mm	100mm	110mm	120mm
Tretlagerabsenkung	48mm	48mm	48mm	48mm
Tretlagerhöhe	301mm	301mm	301mm	301mm
Vorbaulänge	60mm	60mm	80mm	80mm
Überstandshöhe (mm)	668mm	686mm	715mm	745mm